



Paper Strapping

- 100% Recyclable
- Alternative to PET and PP Strapping
- Works with semi-automatic / automatic strapping machines
- Made from FSC accredited paper - smooth finish
- Break strength of 100-122 lbs.



Polyester (PET) and Polypropylene (PP)

- Poly and Paper strap retains tension and keeps goods secure during transport.
- Lightweight and easy to use.
- No sharp edges
- Suitable for semi-and fully automatic strapping heads



Polyester (PET) and polypropylene (PP or Poly) strapping are safer, easier and more economical alternatives to steel strapping. PET is 80% lighter than steel and offers excellent load retention for medium- to heavy-weight applications, including lumber and bricks. PET has more flexibility than steel and less elongation than Poly. Poly (PP) strapping is half the weight of steel and is highly economical for light- to medium-weight loads and general-duty applications.



Hand grade strapping in embossed PP or smooth PET. 16x6 core. PP 350 – 900 lb. break; PET 820 – 1100 lb. break.



Green power tool grade PET strapping. 16x6 core. Smooth or embossed finish. Available in 800, 1400 and 1900 lb. break.



White machine grade strapping. 8x8 core. Embossed finish. Available in 300 or 350 lb. break.

SPECIFICATIONS



PAPER STRAPPING

ITEM	DESCRIPTION	SKID QTY (COILS)	CORE (INCHES)	WIDTH	BREAK STRENGTH (LB)	LENGTH (FEET)	FINISH	COLOR
15800	3/8" Paper Strapping	48	8 x 8"	3/8"	100	6,600	Smooth	Kraft
15801	1/2" Paper Strapping	48	8 x 8"	1/2"	122	6,600	Smooth	Kraft



HAND GRADE

ITEM	DESCRIPTION	SKID QTY (COILS)	CORE (INCHES)	WIDTH	THICKNESS (INCHES)	BREAK STRENGTH (LB)	LENGTH (FEET)	FINISH	COLOR
15200	Black Hand Grade PP	28	16 x 6	1/2"	0.019	350	9000	Embossed	Black
15201	Black Hand Grade PP	28	16 x 6	1/2"	0.024	600	7200	Embossed	Black
15217	Black Hand Grade PP	28	16 x 6	1/2"	0.035	750	5600	Embossed	Black
15233	Black Hand Grade PP	28	8 x 8	1/2"	0.035	750	5600	Embossed	Black
15218	Black Hand Grade PP	28	16 x 6	5/8"	0.035	900	6000	Embossed	Black
15232	Black Hand Grade PP	28	8 x 8	5/8"	0.035	900	6000	Embossed	Black
15229	Black Hand Grade PET	24	16 x 6	5/8"	0.028	820	6500	Smooth	Black
15204	Green Hand Grade PET	24	16 x 6	5/8"	0.025	900	4400	Smooth	Green
15203	Green Hand Grade PET	28	16 x 6	5/8"	0.030	1100	3600	Smooth	Green
15231	Black Hand Grade PET	24	16 x 6	5/8"	0.035	1400	4200	Smooth	Black

POWER TOOL GRADE

ITEM	DESCRIPTION	SKID QTY (COILS)	CORE (INCHES)	WIDTH	THICKNESS (INCHES)	BREAK STRENGTH (LB)	LENGTH (FEET)	FINISH	COLOR
15222	Black Power Tool Grade PET	24	16 x 6	1/2"	0.020	600	7200	Smooth	Black
15209	Green Power Tool Grade PET	12	16 x 6	1/2"	0.028	800	6500	Smooth	Green
15230	Black Power Tool Grade PET	24	16 x 6	5/8"	0.035	1400	3600	Smooth	Black
15227	Green Power Tool Grade PET	28	16 x 6	5/8"	0.040	1600	4000	Smooth	Green
15208	Green Power Tool Grade PET	24	16 x 6	5/8"	0.035	1400	4200	Smooth	Green
15225	Black Power Tool Grade PET	24	16 x 6	3/4"	0.050	2300	2200	Smooth	Black
15210	Green Power Tool Grade PET AAR Grade	24	16 x 6	3/4"	0.040	1900	3000	Smooth	Green
15216	Green Power Tool Grade PET	24	16 x 6	5/8"	0.035	1400	4000	Embossed	Green
15220	Green Power Tool Grade PET AAR Grade	24	16 x 6	3/4"	0.040	1900	3000	Embossed	Green

MACHINE GRADE

ITEM	DESCRIPTION	SKID QTY (COILS)	CORE (INCHES)	WIDTH	THICKNESS (INCHES)	BREAK STRENGTH (LB)	LENGTH (FEET)	FINISH	COLOR
15206	White Machine Grade PP	60	8 x 8	3/8"	0.024	300	12900	Embossed	White
15207	White Machine Grade PP	60	8 x 8	1/2"	0.023	350	9900	Embossed	White
15223	Black Machine Grade PP	60	8 x 8	1/2"	0.024	300	7200	Embossed	Black